

2021 MODEL LINEUP

Engine Type		Sport Boats			Sport Decks					Deck Boats					Cuddies / Cruisers			Center Consoles					Dual Consoles			
		225	225	250	198	204	214	208	215	235	172	182	192	201	212	208	225	250	173	186	206	216	236	191	231	269
		LR	SE	LR	LX	LR	LR	LR/LS	LR	LR	SC	SC	SC	DS	SC	CR	CR	CR	CC	CC	CC	CC	CC	DC	DC	DC
		I/O	I/O	I/O	I/O	O/B	O/B	I/O	I/O	I/O	O/B	O/B	O/B	O/B	O/B	I/O	I/O	I/O	O/B	O/B	O/B	O/B	O/B	O/B	O/B	O/B
Length Overall	in ft	275.00 22'11"	275.00 22'11"	300.00 25'0"	237.00 19'9"	245.00 20'5"	260.00 21'8"	248.50 20'8"	263.00 21'11"	287.00 23'11"	207.00 17'3"	229.50 19'1"	241.50 20'1"	241.50 20'1"	263.60 21'11"	248.50 20'8"	275.00 22'11"	300.00 25'0"	207.00 17'3"	229.50 19'1"	241.50 20'1"	260.00 21'8"	284.00 23'8"	229.50 19'1"	284.00 23'8"	336.00 27'11"
Beam	in cm	100.0 254.0	100.0 254.0	102 259	94.0 238.8	98.5 250.2	101.0 256.5	98.5 250.2	101.0 256.5	101.0 256.5	90.0 228.6	90.0 228.6	100.0 254.0	100.0 254.0	102.0 259.1	98.5 250.2	100 254	102 259	90.0 228.6	90.0 228.6	100.0 254.0	101.0 256.5	101.0 256.5	90.0 228.6	101.0 256.5	102.0 259.1
Bridge Clearance (Standard Windshield)	in cm	52.0 132.1	52.0 132.1	65 165	47.0 119.4	49.0 124.5	58.0 147.3	49.0 124.5	58.0 147.3	58.0 147.3	41.0 104.1	39.0 99.1	50.0 127.0	60.0 152.4	50.0 127.0	49.0 124.5	55 140	65 165	59.0 149.9	59.0 149.9	63 (73) 160 (186)	72.0 182.9	72.0 182.9	50.5 128.3	58.0 147.3	75.0 190.5
Bridge Clearance Ttop/Hardtop w/o External Options	in cm																				96.0 243.8	96.0 243.8	96.0 243.8			105.0 266.7
Average Dry Weight * (w/ popular engine)	lb engine	3364 240HP	3364 240HP	4340 240HP	2828 200HP	2490 115HP	3114 150HP	2974 200HP	3705 240HP	4105 240HP	1900 90HP	2000 90HP	2600 115HP	2800 115HP	3100 150HP	3074 200HP	3539 240HP	4192 240HP	2100 90hp	2300 115HP	2700 140HP	3150 200HP	3648 250HP	2000 90HP	3648 250HP	6200 Twin200HP
Fuel Capacity	gal liter	56 212	56 212	68 257	34 129	39 149	46 174	34 129	46 174	56 212	21 79	21 79	46 174	46 174	57 216	34 129	56 212	68 257	30 114	34 129	46 174	57 216	68 257	21 79	56 212	135 511
Water Capacity	gal liter	6 23	6 23	13 49	6 23	6 23	13 49	6 23	13 49	13 49			3 (13) 11 (49)	3 (13) 11 (49)	3 (13) 11 (49)	6 23	6 23	13 49			13 49	13 49	13 49		13 49	19 72
Ice Box / Cooler Capacity	qt liter	32+25 30+24	32+25 30+24	32+32+25 30+30+24	32+14 30+13	32+14 30+13	25+17 24+16	32+14 30+13	25+17 24+16	25+32 24+30	25+22 24+21	25+22 24+21	67+25+45 63+24+43	67+25+45 63+24+43	67+25+45 63+24+43	25 +24	25 +24	32+25 30+24	48+68 45+64	48+68 45+64	48+68 45+64	74+68 70+64	74+68 70+64	25+22 24+21	25+32 24+30	60+16+185 57+15+80
Livewell Capacity	gal liter				11 42	11 42	11 42	11 42	11 42	11 42	6 23	6 23	11 42	11 42	11 42				15+17 98+64	26+17 98+64	26+17 98+64	14+17 53+64	14+17 53+64	6 23	11 42	15 57
Max Capacity	ppl/lb ppl/kg	10/2080 10/943	10/2080 10/943	10/2265 10/1027	9/1450 9/657	9/1715 9/778	11/2167 11/983	9/1715 9/778	11/2167 11/983	12/2535 12/1150	7/1800 7/816	9/2025 9/918	10/2225 10/1009	10/2225 10/1009	12/2600 12/1179	9/1715 9/778	10/2080 10/943	10/2265 10/1027	6/1775 6/805	7/1875 7/850	9/2400 9/1088	10/3050 10/1383	12/3250 12/1474	9/2025 9/918	12/2535 12/1150	Yahot Cert.
Max Engine Power	hp				150	225					90	115	175	175	200				90	150	200	200	300	115	300	450
Molded Depth (Windshield Base to Keel)	in cm	51.0 129.5	51.0 129.5	66 168	47.0 119.4	48.0 121.9	58.0 147.3	48.0 121.9	58.0 147.3	58.0 147.3	49.5 125.7	46.0 116.8	55.0 139.7	55.0 139.7	55.0 139.7	51.0 129.5	54 137	66 168	63.8 162.1	59.0 149.9	62.0 157.5	68.0 172.7	68.0 172.7	55.0 139.7	58.0 147.3	72.5 184.2
Max Depth (With Standard Windshield)	in cm	58.0 147.3	58.0 147.3	77 196	59.0 149.9	62.0 157.5	72.0 182.9	62.0 157.5	72.0 182.9	72.0 182.9	56.0 142.2	48.0 121.9	63.0 160.0	69.5 176.5	63.0 160.0	64.0 162.6	61 155	77 196	70.0 177.8	71.0 180.3	74.0 188.0	85.0 215.9	85.0 215.9	61.0 154.9	72.0 182.9	91.7 232.9
Max Draft (Drive Down)	in cm	33.0 83.8	33.0 83.8	34 86	32.0 81.3	31.0 78.7	32.0 81.3	34.0 86.4	34.0 86.4	34.0 86.4	28.0 71.1	28.0 71.1	31.5 80.0	31.5 80.0	31.0 78.7	34.0 86.4	34 86	34 86	27.0 68.6	28.0 71.1	31.0 78.7	32.0 81.3	33.0 83.8	28.0 71.1	32.0 81.3	32.4 82.3
Max Draft ^ (Drive Up)	in cm	18.0 45.7	18.0 45.7	17 43	18.0 45.7	18.0 45.7	17.0 43.2	18.0 45.7	17.0 43.2	17.0 43.2	11.5 29.2	12.5 31.8	14.5 36.8	14.5 36.8	14.0 35.6	18.0 45.7	17 43	17 43	11.5 29.2	12.5 31.8	14.0 35.6	15.0 38.1	16.0 40.6	12.5 31.8	17.0 43.2	18.0 45.7
Bow Depth (Bow to Cushion Top)	in cm	20.0 50.8	20.0 50.8	47 119	15.0 38.1	16.0 40.6	17.0 43.2	16.0 40.6	17.0 43.2	17.0 43.2	12.5 31.8	11.5 29.2	10.0 25.4	14.0 35.6	10.0 25.4	27.0 68.6	28 71	32 81	8.5 21.6	NA	9.5 24.1	10.0 25.4	10.0 25.4	11.5 29.2	17.0 43.2	18.0 45.7
Bow Depth (Max Depth)	in cm	34.0 86.4	34.0 86.4	39 99	32.0 81.3	31.5 80.0	33.0 83.8	31.5 80.0	33.0 83.8	33.0 83.8	30.6 77.7	26.4 67.1	26.2 66.6	30.0 76.2	26.4 67.1	45.0 114.3	49 124	58 147	20.5 52.1	21.5 54.6	23.3 59.2	24.0 61.0	24.0 61.0	26.4 67.1	33.0 83.8	38.8 98.6
Bow Length (Max Length)	in cm	59.0 149.9	59.0 149.9	68 173	55.2 140.2	55.2 140.2	59.0 149.9	55.2 140.2	59.0 149.9	59.0 149.9	58.5 148.6	65.0 165.1	65.0 165.1	66.0 167.6	65.0 166.7	66.0 167.6	81 206	68 173	54.0 137.2	55.0 139.7	60.0 152.4	73.0 185.4	73.0 185.4	65.0 165.1	59.0 149.9	67.0 170.2
Cockpit Depth (At Helm)	in cm	33.0 83.8	33.0 83.8	36 91	31.0 78.7	31.8 80.8	34.0 86.4	34.0 86.4	34.0 86.4	34.0 86.4	30.0 76.2	27.0 68.6	27.5 69.9	32.0 81.3	27.5 69.9	34.0 86.4	36 91	36 91	22.0 55.9	23.0 58.4	24.5 62.2	24.5 62.2	24.5 62.2	29.5 74.9	34.0 86.4	39.0 99.1
Cockpit Width (Max Molded)	in cm	81.0 205.7	81.0 205.7	79 201	77.0 195.6	81.0 205.7	81.0 205.7	81.0 205.7	81.0 205.7	81.0 205.7	69.0 175.3	73.0 185.4	84.0 213.4	84.5 214.6	84.0 213.4	81.0 205.7	81 206	79 201	69.0 175.3	70.0 177.8	84.0 213.4	84.0 213.4	84.0 213.4	73.0 185.4	81.0 205.7	82.8 210.2
Cockpit Length (Max Molded)	in cm	103.0 261.6	103.0 261.6	119 302	99.0 251.5	101.0 256.5	107.0 271.8	107.0 256.5	107.0 271.8	120.0 304.8	156.0 396.2	169.0 429.3	156.0 396.2	169.0 429.3	178.0 452.1	85.0 215.9	94 239	119 302	162.0 411.5	170.0 431.8	188.0 477.5	192.0 487.7	208.0 528.3	104.3 264.9	120.0 304.8	241.0 612.1
Sleeping Capacity															2+1	2+1	2+2									
Deadrise	deg	20	20	21	19	20	21	20	21	21	18	19	20	20	20	20	20	21	19	19	20	21	21	19	21	21
Transom Angle	deg	15	15	15	15	15	13	15	15	15	15	15	13	13	13	15	15	15	15	15	15	15	15	15	15	15

Red Data is Indicates Optional Equipment

* Weights vary depending on installed options. Refer to Performance Options for additional information.